

ALU

PVC



ALU

PVC



TECHNICAL SPECIFICATIONS

- 1 pc. Vertical and 2 horizontal copy milling motors are available. (3 x 1.1 kW 18.000 rpm)
- It can process 3 sides of the aluminum profile quickly and precisely without turning it.
- There are 4 pneumatic clamps, 2 vertical and 2 horizontal.
- Horizontal and vertical template follower tips are pneumatic and are available in 3 different diameters as Ø 5, Ø8 and Ø10.
- Horizontal and vertical templates containing standard operations positioned horizontally and vertically
- High precision bearing system, gas shock absorbers and ergonomic arm design that facilitates operations.
- Ruler conveyors on the right and left
- Cooling system

TECHNICAL DATA						
TECHNICAL FEATURES						
			BAR	Air cons.		
CR 500	1.1 kW x 3 220V 300Hz	18000 RPM	6-8 Bar	10 Lt/min.	90x110x180 cm	260 kg

TECHNICAL SPECIFICATIONS

- 1 pc. Vertical and 2 horizontal copy milling motors are available. (3 x 1.1 kW 18.000 rpm)
- It can process 3 sides of the PVC profile quickly and precisely without turning it.
- There are 4 pneumatic clamps, 2 vertical and 2 horizontal.
- Horizontal and vertical ends are pneumatic and have 3 different diameters as Ø 11, Ø16 and Ø18.
- Quick and easy to use without the need for templates
- Provides ease of use with its ergonomic handle design
- There is a metering and holding system on the right and left sides.

TECHNICAL DATA						
TECHNICAL FEATURES						
			BAR	Air cons.		
PD 100	2 kW x 1 1.1 kW x 2 220V 300Hz	18000 RPM	6-8 Bar	10 Lt/min.	90x70x160 cm	180 kg