PVC



**DOUBLE BLADED** 

**TAMING END MILLING MACHINE** 





## TECHNICAL SPECIFICATIONS

- · PVC and aluminum profiles in the midde register is designed to familiarize

  Mechanical works as automatic
- andmanval
- · According to four different profiles of adjustable recline system.
- Two corner one of the profile in 20
- seconds makes the milling process.

  Makes milling various angles.
- · Level change (Speed Setting) is
- done as pneumatic
- Designed in accordance with the CE.

	TECHNICAL DATA								
TECHNICAL FEATURES	□	D d			BAR	Air cons.	WXLXH	(KG)	
PAC-502	1.1 kW 400V 50Hz	D=150mm (max) d=30 mm	3000 D/min. RPM	K=80mm(max) S=75mm(max) Q=	6-8 Bar	5 Lt/min	81x55x120 cm	105 kg	







## TECHNICAL SPECIFICATIONS

- PVC and aluminum profiles in the midde register is designed to familiarize

  Mechanical works as automatic
- andmanval
- · According to four different profiles of adjustable recline system.
- Two corner one of the profile in 20
- seconds makes the milling process.

  Makes milling various angles.
- · Level change (Speed Setting) is done as pneumatic
- Designed in accordance with the CE.

	TECHNICAL DATA									
TECHNI FEATUR		D d			BAR	Air cons.	WXLXH	(NG)		
PAO-5	1.1 kW 400V 50Hz	D=150mm (max) d=30 mm	3000 D/min. RPM	K=80mm(max) S=75mm(max) Q=	6-8 Bar	5 Lt/min	81x55x120 cm	95 kg		







