











## TECHNICAL SPECIFICATIONS

- · Designed for cutting processes of aluminium and plastic profiles
- Specially alloyed aluminium table,long-lasting electrostatic paint
- Pneumatic cutting process, automatic running system
- · Protection cover with security switch
- Adjustment of cutting speed according to profile

- · Cutting feature to left and right at standard 15°-22,5°-30°-45°-90° free cutting at various angles
- Manual clip of profiles.
- · Designed in accordance with the CE

TECHNICAL DATA								
TECHNICAL FEATURES	<b>4</b>	D d		BAR Air cons.		WXLXH	(KG	
PC 400	2,2 kW 400V~3N PE 50 Hz	Max.Ø400 mm	3000 D/min. RPM			68x60x70 cm	70 kg	







## TECHNICAL SPECIFICATIONS

- · Double speed main engine

- Saw clearance removal system
- Boron oil circulation pump and tank for saw cooling and chip removal
- · Emergency stop button
- Adjustable fixing arm to cut to the same size
  45° right, 45° left cut
  24V Control System
  24V Control System

  - · Holding the piece from the closest area to the saw with the movable jaw system in the vise
  - Burr-free cut

	TECHNICAL DATA										
TECHNICA FEATURES		D d		BAR Air cons.		WXLXH	(NG)				
TT 315	1.5 kW 400V 50Hz	D=315 mm d=32 mm	115 D/min. RPM	6-8 Bar	35 Lt/min.	98x53x120 cm	102 kg				







