



SM 2200

PVC SASH HARDWARE MOUNTING STATION (MULTIFUNCTIONS)

GLAZING UNIT

SCM 400



PVC



TECHNICAL SPECIFICATIONS

- Ease of PVC sash frames hardware assembly.
- Top and bottom shelves for hardware.
- Cuts double opening hardware with requested measurements and screws them on frame.
- Single opening espagnolette on door sashes can be mounted.
- Single and double opening sash hardware can be mounted.
- Triple drilling and espagnolette hole opening on sash frames.
- Drills hinge and pin holes on right and left sashes.



ALU

PVC



TECHNICAL SPECIFICATIONS

- Fast installation of glass on the windows and doors.
- Glazed joinery transferring to package on rollers.
- Parallel block clamps allow you to set an appropriate balance.
- Raising the work piece up provides easy installation

TECHNICAL DATA

TECHNICAL FEATURES								
					BAR	Air cons.		
SM 2200	1.6 kW 400V 50Hz	D=9 mm h=22 mm d=3 mm	S= 100mm (min) K=115mm (min)	amin= 400mm amax= 2200mm bmin= 400mm bmax= 2200mm	6-8 Bar	60 Lt/min.	3100x3100x2000 cm	600 kg

TECHNICAL DATA

TECHNICAL FEATURES					
		BAR	Air cons.		
SCM 400	amax= 2700mm bmin= 400mm	6-8 Bar	10 Lt/min.	104x303x202 cm	400 kg