





- Perpendicular position Screwing machine
- · Adjustment of a basic condition for different profiles
- Pneumatic driving and management of the machine tool
- For practical works, management of a pedal
 Automatic horizontal fixing of a structure is carried out by means of a pneumatic clip
- · An automatic power unit
- · Adjustment of depth screwing
- The area of work (operation screwing) 35-95 mm
- System standard metrage.
- · Time screwing a screw on a basic tin on the average.

	TECHNICAL DATA									
TECHNICAL FEATURES		- D - d - d - d - d - d - d - d - d - d	, , , , , , , , , , , , , , , , , , ,							
SV-520	HP 0.52 Kw 0.39 r min 1180 r max 2500	D = 9 mm h = 22 mm d = 3 mm	L max=150 mm h max=90 mm L min=20 mm h min=30mm	6-8 Bar	F=265 cm W=185 cm L=45 cm					





TECHNICAL SPECIFICATIONS

- Perpendicular position Screwing machine
- · Adjustment of a basic condition for different profiles Pneumatic driving and management of the machine tool

- For practical works, management of a pedal
 Automatic horizontal fixing of a structure is carried out by means of a pneumatic clip
- · Adjustment of depth screwing
- · The area of work (operation screwing) 35-95 mm
- System standard metrage.
- · Time screwing a screw on a basic tin on the average.

TECHNICAL DATA									
TECHNICAL FEATURES		- 0 - 4 - 4 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7			I.B.				
SV-520 M	HP 0.52 Kw 0.39 r min 1180 r max 2500	D = 9 mm h = 22 mm d = 3 mm	L max=150 mm h max=90 mm L min=20 mm h min=30mm	6-8 Bar	F=265 cm W=185 cm L=45 cm				





